

RAISED STEEL PANEL



CHOOSE YOUR OPTIONS

| INSULATION | ThermoGuard™ | ThermoSteel™ | TS-138 | Series 24 | ValuCraft Plus |
|-----------------------------------|--------------|--------------|-------------|------------------------|------------------------|
| Foam/Insulate | Polyurethane | Polystyrene | Polystyrene | Plain Steel/ T-Bond | Plain Steel/ T-Bond |
| R-Value | 18.0 | 9.25 | 7.50 | T-Bond: 7.0 | T-Bond: 7.0 |
| U-Factor (Btu/hr/ft2/F) | 0.14 | 0.22 | 0.26 | 0.38 | 0.38 |
| Thickness | 2 inches | 2 inches | 1¾ inches | 2 inches | 2 inches |
| Exterior Steel | 27 gauge | 25 gauge | 27 gauge | 24 gauge | 25 gauge |
| Interior Steel | 27 gauge | 26 gauge | 27 gauge | N/A | N/A |
| Warranty* <i>Excludes Springs</i> | Lifetime | Lifetime | 25 years | Lifetime | 25 years |

COLORS

| | | | | | |
|----------------|---|---|---|---|---|
| White | • | • | • | • | • |
| Almond | • | | • | • | • |
| Sandtone | • | • | • | • | • |
| Tera-Bronze | • | • | • | • | • |
| Green | • | | • | | |
| Gray | • | | • | | |
| Coffee | • | • | • | • | • |
| Black | • | • | • | • | • |
| Light Oak | • | • | • | • | • |
| Dark Oak | • | • | • | • | • |
| Weathered Oak | • | | • | | |
| Rosewood | | • | | | |
| Color Select** | • | • | • | • | • |

*For full warranty details contact your Midland dealer

**ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.




WINDOWS



COLORS



GLASS



*Tempered only. All other glass is available in both tempered and untempered.